

## **Model 8700** X-Ray Pulse Counter & **Exposure Time Meter**

The Model 8700 is a versatile digital x-ray pulse counter and exposure time meter. It measures the time or duration of radiation output produced by a wide variety of x-ray generators.

For direct measurement of exposure from the x-ray head, simply place the 8700 under the head and make an exposure. The 8700 is "self-resetting." There is no need to reset the instrument after each reading. The reading is stored after each exposure, until the next exposure

When testing x-ray timers and controls, the time of the relay contact closure can be measured using the AC input feature. When used with DC, capacitor discharge and 3-phase x-ray, exposure time is measured in milliseconds.

Typical applications include: verification of x-ray exposure time, calibration of x-ray timer, quality assurance, measurement of exposure, direct measurement of timer accuracy, and analysis of x-ray malfunctions.

An optional remote sensor is available to allow use of the 8700 at distances of up to 12 feet away from the x-ray machine.

## **Features:**

- ► High Accuracy
- ▶ Use for Medical or Dental X-rays
- ▶ Small Hand-Held Size
- ▶ Battery Operated
- ► Two year Warranty



## **Accessories**

Model 8700RS	Remote sensor with 3 meter cable
Model 8700SC	Oscilloscope cable

## **Specifications**

Specifications	
	4 digit, o.4 in (10.2 mm) liquid crystal
Range:	
Accuracy:	gggg minisconus
AC:	+/- 1 count
DC:	2%, ± 1 millisecond
X-Ray Detection:	+/- 1 count
Sensitivity:	
X-ray input:	50 kVp, 5 mA at 5 cm from top surface of
	case, pointed to target on case
AC input:	65 VAC minimum, 130 VAC maximum
Controls:	three position switch, pulse, off, milliseconds,
	illuminated pushbutton with green power-on
	indication
Output:	analog waveform to oscilloscope, 3.9 mm
	jack
Power:	9 V, accessible from bottom of case
Battery life:	24 hours continuous, typically 6 months of normal use, low battery indicator on display
Dimensions:	8.0 x 14.7 x 4.0 cm (3.15 x 5.8 x 1.6 in)
Weight:	o.5 kg (1.1 lb)

